

CUTTING SECTION

Continuous rim discs



Ø	rim thickness	core thickness	standard bore	rim height
200	2,0	1,6 mm	30	8,0
200	2,2	1,6 mm	30	8,0
250	1,2	1,6 rect.	60	8,0
250	1,4	1,6 rect.	60	8,0
250	1,6	1,6 rect.	60	8,0
250	1,8	1,6 rect.	60	8,0
250	2,0	1,6 mm	60	8,0
250	2,2	1,6 mm	60	8,0
250	2,4	1,6 mm	60	8,0
300/306	1,2	1,6 rect.	60	8,0/11,0
300/306	1,4	1,6 rect.	60	8,0/11,0
300/306	1,6	1,6 rect.	60	8,0/11,0
300/306	1,8	1,6 rect.	60	8,0/11,0
300/306	2,0	1,6 mm	60	8,0/11,0
300/306	2,2	1,6 mm	60	8,0/11,0
300/306	2,4	1,6 mm	60	8,0/11,0
300/306	2,6	1,8 mm	60	8,0/11,0
300/306	2,8	1,8 mm	60	8,0/11,0
300/306	3,0	1,8 mm	60	8,0/11,0
300/306	3,5	2,2 mm	60	8,0
300/306	4,0	2,2 mm	60	8,0
300	4,6	2,2 mm	60	8,0
300	4,8	2,2 mm	60	8,0
300	5,0	2,2 mm	60	8,0